
Bulkhead and Panel Mounted Jack–Jack Adapters (Connect two plugs)










Figure 1 (Bulkhead mount, hermetically sealed)

Figure 2 (Panel mount)

Figure	Dimensions		Max.	Mounting	Plating		Delta P/N
	A	В	Panel	Figure	Body	Contact	Deita P/N
1	1.54	.863	.25	72	Nickel	Silver (C)	UG-30D/U
1	1.54	.863	.25	72	Nickel	Silver (C)	UG-30E/U
1	1.54	.863	.25	72	Silver	Gold (C)	M55339/04-00030
1	2.06	1.375	.75	72	Nickel	Silver (C)	1126-000-N728
2	1.75	1.00	_	33	Nickel	Silver (C)	1125-000-N330

Straight Adapters

Figure 1 (Straight jack-jack; connects two plugs)




Figure 2 (Straight plug-plug; connects two jacks)




Figure 3 (Straight jack–plug; connects one plug and one jack)




Figure	Dimensions		Pla	ating	Delta P/N
	A	В	Body	Contact	Delta P/N
1	1.75	.66	Nickel	Silver (C)	UG-29B/U
1	1.75	.66	Silver	Gold (C)	M55339/07-00029
2	1.59	.78	Nickel	Silver (C)	UG-57B/U
2	1.59	.78	Silver	Gold (C)	M55339/05-00057*
3	1.56	.78	Nickel	Silver (C)	1134-000-N000

^{*} Lockwire holes in coupling nut.

(C) in contact plating column indicates captive contact. • See page 203 for mounting dimensions.

See page 6 for alternate body plating information.