

Right Angle Adapters




Figure 1 (Right angle plug-jack; connects one plug and one jack)




Figure 2 (Right angle plug-plug; connects two jacks)




Figure 3
(Bulkhead mounted right angle jack-jack; connects two plugs)

Figure	Dimensions		Max.	Mounting	Plating		Delta P/N
	Α	В	Panel	Figure	Body	Contact	Deita 17 N
1	1.30	1.38	_	_	Nickel	Silver (C)	UG-27C/U
1	1.30	1.38	_		Nickel	Gold (C)	UG-27D/U
1	1.30	1.38	 		Silver	Gold (C)	M55339/03-00027*
2	1.39	1.39			Nickel	Silver (C)	1137-000-N000
3	2.13	1.36	.25	72	Nickel	Gold (C)	UG-202A/U

^{*} Lockwire holes in coupling nut.

Tee Adapters




Figure 1 (Tee jack-jack; connects three plugs)




Figure 2 (Tee jack-plug-jack; connects two plugs and one jack)




Figure 3 (Tee jack-jack-plug; connects two plugs and one jack)

88

Figure	Dimensions		PI	ating	Delta P/N
	Α	В	Body	Contact	Deita F/N
1	1.75	1.22	Nickel	Silver (C)	UG-28A/U
1	1.75	1.22	Silver	Gold (C)	M55339/06-00028
2	1.75	1.47	Nickel	Silver (C)	UG-107B/U
2	1.75	1.47	Silver	Gold (C)	M55339/06-00001
3	2.03	1.22	Nickel	Gold (C)	1149-000-N001-1

(C) in contact plating column indicates captive contact. • See page 203 for mounting dimensions.

See page 6 for alternate body plating information.