

Straight Plug—Military Clamp for Flexible Cable




Figure 1
(Standard coupling nut)




Figure 2
(Safety-wire holes in coupling nut)




Figure 3
(Standard coupling nut)




Figure 4
(Safety-wire holes in coupling nut)

Cable Group	Figure	Dimensions		Plating		Delta P/N	Assembly Procedure/ Trim Code
		A	B	Body	Contact		
1	1	1.66	.75	Nickel	Gold	1201-001-N000	A/01
2, 3	1	1.66	.75	Nickel	Gold	1201-004-N000	A/01
2, 3	1	1.66	.75	Nickel	Gold (C)	1201-004-N001-4	A/01
2, 3	2	1.66	.75	Nickel	Gold	1240-004-N000	A/01
2, 3	2	1.66	.75	Nickel	Gold (C)	1240-004-N001	A/01
5, 6	3	1.09	.50	Nickel	Gold	1201-015-N000	A/17
5, 6	3	1.09	.50	Nickel	Gold (C)	1201-015-N001	A/17
5, 6	4	1.09	.50	Nickel	Gold	1240-015-N000	A/17
5, 6	4	1.09	.50	Nickel	Gold (C)	1240-015-N001	A/17
7	3	1.09	.50	Nickel	Gold	1201-021-N000	A/17
7	3	1.09	.50	Nickel	Gold (C)	1201-021-N001	A/17
7	4	1.09	.50	Nickel	Gold	1240-021-N000	A/17
7	4	1.09	.50	Nickel	Gold (C)	1240-021-N001	A/17
8A	3	1.09	.50	Nickel	Gold	1201-029-N000	A/17
8A	3	1.09	.50	Nickel	Gold (C)	1201-029-N001	A/17
8B	3	1.09	.50	Nickel	Gold	1201-043-N000	A/17
8B	3	1.09	.50	Nickel	Gold (C)	1201-043-N001	A/17
9	3	1.09	.50	Nickel	Gold	1201-036-N000	A/18
9	3	1.09	.50	Nickel	Gold (C)	1201-036-N001-2	A/18
9	4	1.09	.50	Nickel	Gold	1240-036-N000	A/18
9	4	1.09	.50	Nickel	Gold (C)	1240-036-N001	A/18
11	3	1.09	.50	Nickel	Gold	1201-038-N000	A/18
11	3	1.09	.50	Nickel	Gold (C)	1201-038-N001	A/18

See page 204 for cable groups. • Assembly procedures start on page 205.
(C) in contact plating column indicates captive contact. • See page 6 for alternate body plating information.