

Straight Jacks—For Flexible and Semi-Rigid Cable




Figure 1




Figure 2





Figure 3

See page 199 for MIL-PRF-39012 QPL versions.

Heli-Grip® Cable Attachment (where noted)



These connectors have captivated contacts and allow rapid, easy assembly—simply trim the cable, slide into the cone/insulator/contact assembly (left), solder the center conductor to the contact, and screw body assembly (right) onto the cable assembly.

Military Clamp for Flexible Cable

Cable Group	Figure	Dimensions		Plating		Delta P/N	Assembly Procedure/ Trim Code
		A	B	Body	Contact		
1	1	1.75	.75	Nickel	Gold	1208-001-N000	A/20
2, 3	1	1.75	.75	Nickel	Gold	1208-004-N000	A/20
5, 6	2	1.16	.50	Nickel	Gold	1208-015-N000	A/17
5, 6	2	1.16	.50	Nickel	Gold (C)	1208-015-N001	A/17
7	2	1.16	.50	Nickel	Gold	1208-021-N000	A/17
7	2	1.16	.50	Nickel	Gold (C)	1208-021-N001	A/17
9	2	1.16	.50	Nickel	Gold	1208-036-N000	A/18
9	2	1.16	.50	Nickel	Gold (C)	1208-036-N001	A/18
11	2	1.16	.50	Nickel	Gold	1208-038-N000	A/18

Heli-Grip for Flexible Cable

5, 6 [§]	2	1.16	.50	Nickel	Silver (C)	1208-018-N005-1	E/03
RG-223	2	1.16	.50	Nickel	Silver (C)	1208-015-N005	E/03
7	2	1.16	.50	Nickel	Silver (C)	1208-019-N005	E/03
8A	2	1.16	.50	Nickel	Silver (C)	1208-029-N005	E/03
8B	2	1.16	.50	Nickel	Silver (C)	1208-043-N005	E/03
9	2	1.16	.50	Nickel	Silver (C)	1208-037-N005	E/03
10	2	1.16	.50	Nickel	Silver (C)	1208-100-N005	E/03
11	2	1.16	.50	Nickel	Silver (C)	1208-038-N005	E/03

Crimp Type for Flexible Cable

5	3	1.16	.50	Nickel	Gold	1210-017-N000	B/05
6	3	1.16	.50	Nickel	Gold	1210-013-N000	B/05
7	3	1.16	.50	Nickel	Gold	1210-020-N000	B/05
7	3	1.06	.41	Nickel	Silver	1210-020-N001**	***

Solder-Clamp for Semi-Rigid Cable

13	2	1.16	.50	Nickel*	Gold	1208-031-N003	F/08
14	2	1.16	.50	Nickel*	Gold	1208-025-N003	F/07

[§]Except RG-223/U.

*Solder ferrule is gold plated.

See page 204 for cable groups. • Assembly procedures start on page 205.
(C) in contact plating column indicates captive contact. • See page 6 for alternate body plating information.
Indicates crimp center contact. • *Contact factory for cable assembly instructions.