


DASH NO.	M CODE	MADE FROM
----------	--------	-----------

GSD

1705-1

REVISIONS	
ISSUE	CHANGES
6	CN 32731 C REDRAWN KH 12/10/90
7	CN 35381 E MJB 03/30/94
8	CN 37799 E TML 03/09/99
9	CN 39699 C DCT 11/14/6



NOTES:

1. FOR USE WITH RG-59, 62 & 210/U CABLE.
2. FOR CABLING INSTRUCTIONS SEE CP-441.
3. FOR CABLE TRIMMING USE KTJ-72 & KTD-134.
4. FOR CRIMPING USE DIE KTH-2062.
5. MATERIALS:
INSULATOR: TEFLON, ASTM-D-4894
GASKET: SIL. RUB., A-A-59588
K-GRIP SLEEVE: COMMERCIAL BRONZE TUBE, ASTM-B135
SPRING WASHER & CONTACTS: BER. COP., ASTM-B-196
ALL OTHER PARTS: BRASS, ASTM-B16
6. FINISHES:
CENTER CONTACT: HARD GOLD PLT. PER ASTM-B488
ALL OTHER METAL PARTS: KINGS TARNISH RESISTANT FINISH (TR-5)
7. ELECTRICAL CHARACTERISTICS:
OPERATING VOLTAGE: 3500 VOLTS AC
5000 VOLTS DC
8. DIMENSIONS IN INCHES [MM].

SCALE 4:1	
APPROX SURFACE AREA	
USED ON	
REF: N.B.S. ND-545C	
PLUG, SHV	
DRAWN JCA	DATE 12/10/90
DESIGN LJ	DATE 12/11/90
APPR.	DATE
 ROCK HILL, SOUTH CAROLINA 29730	
1705-1	

GSD