






Socket connector



Directive 2002/95/EC
"RoHS"
Compliant



without strain relief



with strain relief (installed)



strain relief

Strain relief must be ordered separately

TECHNICAL DATA

Insulators:	Polyester GV, VO, UL 94, grey RAL 7035
Operating temperature range:	-65° C to +150° C
Current carrying capacity:	1 A
Test voltage:	1000 V
Contacts:	Copper alloy

No. of Pos.	A ± 0.1	B ± 0.2
6	2 X 2.54 = 5.08	12.30
8	3 X 2.54 = 7.62	14.80
10	4 X 2.54 = 10.16	17.30
14	6 X 2.54 = 15.24	22.40
16	7 X 2.54 = 17.78	24.90
20	9 X 2.54 = 22.86	30.00
26	12 X 2.54 = 30.48	37.60
34	16 X 2.54 = 40.64	47.80
40	19 X 2.54 = 48.26	55.40
50	24 X 2.54 = 60.96	68.10
60	29 X 2.54 = 73.66	80.80
64	31 X 2.54 = 78.74	85.85

Part Numbers

Kat 1 i HKA

No. of Pos.	Socket Connector	Strain Relief
6	142 A 10199 X	
8	142 A 10209 X	
10	142 A 10219 X	140 X 10059 X
14	142 A 10229 X	140 X 10069 X
16	142 A 10239 X	140 X 10079 X
20	142 A 10249 X	140 X 10089 X
26	142 A 10259 X	140 X 10099 X
34	142 A 10269 X	140 X 10109 X

40	142 A 10279 X	140 X 10119 X
50	142 A 10289 X	140 X 10129 X
60	142 A 10299 X	140 X 10139 X
64	142 A 10419 X	140 X 10159 X