

Xtreme-Marine®


Undersea Video Cable

Designed with precision coaxial components for SD/HD video and ideal for depths up to 7KM, our robust Xtreme-Marine® cable is designed with our full water-blocked technology, an improved strength member and the Subsea industry-preferred choice of Winchester's "Xtreme-Grade" Polyurethane jackets.



KEY FEATURES

- Full water-blocked technology with improved strength member
- RG 6F Premium coax design for SD & HD achievable video transmission, with length limitations per Winchester's "Xtreme Marine® HD" coax chart, when properly terminated with premium BNC/TNC style terminations
- Flexible designs which are ideal for high flexing applications
- Available in fiber optic cables (Xtreme-Marine® E0)
- Custom design options available
- RoHS and REACH compliant



APPLICATIONS

- Pipe and well inspection
- Robotics
- Fisheries
- Water theme entertainment
- Marine movie production
- ROV
- Diver Umbilical
- Overboard drop camera
- Topside marine environments
- Subsea monitoring
- Ocean observatory

PART NUMBERS

Part Number	Description						Insulation Material	
FM020914S-1**	11 x 16AWG (1.32 mm ²)	RG 6F 22AWG	2,700	0.062	0.535	13.6	161	
FM020914S-2**	12 x 18AWG (1.00 mm ²)	RG 6F 22AWG	2,700	0.054	0.472	12.0	155	
FM020914S-3**	12 x 20AWG (.52 mm ²)	RG 6F 22AWG	2,700	0.047	0.454	11.5	115	
FM020914S-4**	8 x 16AWG (1.32 mm ²)	Mini 59 26AWG	2,700	0.058	0.445	11.3	118	
FM020914S-5*	10 x 18AWG (1.0 mm ²)	Mini 59 26AWG	2,700	0.056	0.425	10.8	142	
FM020914S-6*	14 x 22AWG (.38 mm ²)	Mini 59 26AWG	2,700	0.056	0.390	9.9	106	
FM020914S-7*	12 x 22AWG (.38 mm ²)	Mini 59 26AWG	1,400	0.046	0.355	9.0	95	
FM020914S-8*	12 x 22AWG (.38 mm ²)	1x Micro 28AWG	1,400	0.045	0.305	7.7	75	
FM020914S-9**	2 x 16AWG (1.32 mm ²)	1x Micro 28AWG	1,400	0.050	0.342	8.7	66	
FM020914S-10**	6 x 16AWG 2 tsp 22AWG 2 x UTP 26AWG 100 Ohm	1x RG 59 22AWG	2,700	0.062	0.560	14.2	140	
FM020914S-11**	2 x 18AWG 2x 22AWG (300v)	1x Mini 59 26AWG	1,400	0.050	0.340	8.6	63	
FM020914S-12**	1TSP 16AWG, 1TSP 20AWG 1TP 26AWG 1 x16 overall shld	1x Mini 59 26AWG	1,400	0.065	0.440	11.2	112	
FM020914S-13**	1TT 18AWG, 1TSP 24 1UTP 24 100 Ohm 2 x 22AWG	1x Mini 59 26AWG	1,400	0.052	0.440	11.2	102	

* P/N with 300V rating ** P/N with 600V rating

- Higher strength ratings may be ordered up to 50,000 lbs.

- Armored versions incorporating braided stainless steel or dual served steel alloys are also available as special order

Dayville
349 Lake Road
Dayville, CT 06241

San Marcos
1810 Diamond St.
San Marcos, CA 92078

Empalme, Mexico
Edificio 54 Parque Industrial Bella Vista
Carretera Internacional KM.1969
Empalme, Sonora México, 85340