


1007-013-A00E-3

.381 DIA REF



NOTES

1. ASSEMBLED CONNECTOR INTERFACE IS DESIGNED IN ACCORDANCE WITH MIL-STD-348.

2. MATERIAL: CONTACT (F) - BERYLLIUM COPPER PER ASTM B196
INSULATORS - TEFLON PER ASTM D4894
GASKET - SILICONE RUBBER PER A-A-59588
CRIMP SLEEVE - D.H.P. COPPER CDA ALLOY 122
SPRING WASHERS - BERYLLIUM COPPER PER ASTM B196
ALL OTHER PARTS - BRASS PER ASTM B16

3. FINISHES: CONTACTS - GOLD PLATE PER ASTM B488
SPRING WASHERS - NICKEL PLATE PER AMS-QQ-N-290
ALL OTHER PLATED PARTS - SILVER PLATE PER ASTM-B700

UNLESS OTHERWISE SPECIFIED: TOLERANCES: 3 PLACES = $\pm .005$, 2 PLACES = $\pm .02$, ANGLES = $\pm 1/2^\circ$, SURFACE FINISH = 63

THESE DRAWINGS AND SPECIFICATIONS ARE THE PROPERTY OF DELTA ELECTRONICS MFG CORP. AND SHALL NOT BE REPRODUCED, OR COPIED OR USED AS THE BASIS FOR THE MANUFACTURE OR SALE OF APPARATUS OR DEVICES WITHOUT THEIR EXPRESS WRITTEN CONSENT.

M39012/20-0007

DELTA ELECTRONICS MFG. CORP. Beverly, MA 01915

TITLE: "BNC" RIGHT ANGLE CRIMP PLUG FOR
RG-142, 223, & 400/U CABLES

Drawn by	Scale	Ckd. by	Engr Appd	FILE NAME:
BJM	2/1	MR	MR	1007013A00E-003T
10/6/04				

CODE IDENT: -00795

1007-013-A00E-3